

**DESCRIPTION**

Water-based paste formulated with sand, lamellar charges and special binders which make the product extremely hard and elastic. Resins and inert substances are especially resistant to alkaline substrates and atmospheric agents, thus making K29 the ideal solution to fill holes and cracking and restore any missing material, above all outdoors. K29 is a fast drying filler that forms a hard and compact mass on which screws and nails grip easily.

**PERFORMANCE DATA**

	Method	Value
Specific weight	ISO 2811-1	1750–1950 g/l
Drying time	CAP - PF2	fully 24h
Solid by weight	CAP - PF25	85-89 %

**SHELF LIFE**

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

**COLOUR RANGE**

Grey

**TYPICAL USE**

K29 is applied ready for use on different types of surfaces such as plaster, cement and wood: it is also used for thick coats without posing any risk of cracking. The part that needs to be filled must be preliminarily treated with *Acrilifix*.

**TOOLS**

Spatula

**THINNING**

Ready to use.

**APPLY**

+5°C +30°C

**SPECIFICATION ITEM**

Water-based paste filler, ideal for filling holes and cracking or fill missing material, especially outdoors, which forms a tough and compact mass on which screws and nails grip easily.

**INSTRUCTIONS**

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.