

DESCRIPTION

Additive in aqueous dispersion of a fungicide effective against various species of mould and insoluble in water, a characteristic that helps keep the treated surface unaltered and intact for a long time. It is used as an additive in breathable and washable interiors.

PROPERTY OF THE PRODUCT

	Value	Method
Solid by weight	2.5 – 3.5 %	Internal PF25

SPECIFIC

Specific weight	975–1025 g/l	Internal PF3
------------------------	--------------	--------------

SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

TYPICAL USE

The anti-mould A10 is added to water-based paints (2 litres every 14 litres of paint), with the tin being shaken well before use.

SPECIFICATION ITEM

Aqueous dispersion of an efficient fungicide against various species of moulds, insoluble in water. This special feature contributes to keeping the treated surface unaltered and intact for prolonged periods of time.

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.