

DESCRIPTION

Wood dye mixable with water or acetone. It highlights the wood fibers without covering them.

COMPOSITION

Transparent pigments dispersed in solvent.

PRODUCT FEATURES

	VALUE	METHOD
SOLID BY WEIGHT	5-7%	Internal PF25

SPECIFICATION DATA

	VALUE	METHOD
SPECIFIC WEIGHT	950-1050 g/l	Internal PF3
DRYING	Overcoatable 30 minutes if diluted with acetone Overcoatable 8 ore if diluted with water Complete 12 h	Internal PF2

STORAGE

The product should be stored in its original containers at temperatures of between +5°C and +30°C.

COLOURS

Giallo, Rosso, Nero, Mogano, Noce. The colors are not resistant in exterior. It is advisable to check the colour with preliminary tests before application, since the original colour of each type of wood produces a different final shade. The colour between one production and another can be slightly different, so it is necessary to finish a job with the same production.

USE

It is used to paint objects intended for light wood in walnut, mahogany and any other wood colours obtained by mixing the colours red, yellow and black. It can be put in small quantities in all paints to paint them. It is always advisable to check the colour with preliminary tests before application, since the original colour of each type of wood produces a different final shade. It can be over-applied with any type of varnish.

TOOLS

Sponge, Cloth, Spray, Dipping.

THINNING

400% by volume with water or acetone

COVERAGE

13-17 m²/l per coat.

APPLICATION TEMPERATURE SPECIFICATION ITEM INSTRUCTIONS

+5°C +30°C

Transparent dye for wooden items for interiors, mixable with water or acetone to be applied with an average consumption of 67 ml / m².

To carry out the work in a workmanlike method, it is of fundamental importance to follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books, in the application cycle and in the product data sheet. This technical information is intended as a rough guide. Adapt the instructions to the specific conditions of use. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between one operation and the next vary. Our recommendations on the use of the product are based on accurate observations and research carried out by us. The experience gained in practice was also taken into consideration. However, because of the enormous variety of

media and application conditions, it is essential to check the suitability of the product and its effectiveness by testing on the specific case.