

Capwhite Active

Anti-mould breathable water-based paint with high coverage and white point



Interior water-based anti-mold wall paint with high breathability and high whiteness. Easy to apply, it has drying times that allow rapid reoccupation of living spaces. Ideal for professional use, it offers excellent compatibility, adhesion, filling capacity, and coverage on various substrates.

It is enhanced with a fungicide to ensure resistance against mold growth on walls, effective against multiple species and water-insoluble, a feature that helps maintain the treated surface intact and durable over time.



linea **SANACAP**



**HIGH BREATHABILITY
ANTI-MOLD
LONG-LASTING FUNGICIDAL ACTION**



**HIGH WHITENESS
OPAQUE, FULL-COVERAGE FINISH**



**DIRT-RESISTANT
HIGH FILLING POWER**



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Capwhite Active

Anti-mould breathable water-based paint with high coverage and white point

COMPOSITION

APEO-free product formulated with vinyl acetate/acrylate resins in aqueous dispersion and selected fillers

CHARACTERISTICS

Interior water-based wall paint with high breathability and high whiteness, easy to apply, with drying times that allow rapid reoccupation of living spaces. Ideal for professional use, it offers excellent compatibility, adhesion,

filling power, and coverage on various types of substrates

APPLICATION FIELD

Suitable for decorating and protecting a wide range of substrates, both new and under maintenance, including various types of plaster (cement-based, lime-based, premixed), concrete and fiber cement, plasterboard, stucco finishes, and old paints. Ideal wherever fast and cost-effective maintenance is required

AESTHETIC EFFECT

Its high quality provides both aesthetic and technical solutions for different painting needs with a good level of finish. Produces a film with low dust retention that is easy to clean with a damp sponge

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Roller, brush, spray
SUBSTRATE	Free from dust, properly pretreated
COVERAGE	8–10 m ² /l per coat
GLOSS	<5
DRY SOLID CONTENT BY WEIGHT	65–69% by weight
DRYING TIME	Recoat after 4–6 h, fully dry in 5 days
DILUTION	Roller, brush: 20–30% with water by volume Airless spray: 0–10% with water by volume
APPLICATION CONDITIONS	Application temperature: +5°C to +30°C

For more information on the product and application process, please refer to the technical data sheet available at www.caparreghini.it

COLORS AVAILABLE IN STOCK

WHITE

PACKAGING: 4L - 14L



CAP ARREGHINI SpA - ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with UNI EN ISO 9001 - UNI EN ISO 14001 Certified System

Follow us on



www.caparreghini.it

