# Classic W

Water-based protective woodstain



Water-based wood impregnating agent, available in clear or transparent tinted versions. It offers excellent penetration, easy application, and a finish that enhances the natural grain of the wood. The product ensures an odourless application and a low environmental impact, preserving user comfort and safety.

Designed for the protection of wooden structures and items used both outdoors and indoors, such as roof beams, fences, gazebos, windows, doors, cornices, urban furniture, garden furniture, beams, and matchboarding.

## linea NOVOLEGNO



EXCELLENT WEATHER RESISTANCE
DEEP PENETRATION
NOURISHES AND PROTECTS THE WOOD



HIGHLIGHTS THE WOOD GRAIN UNIFORM COLOUR TONE



ARREGHIN

EASY TO APPLY
ODOURLESS
LOW ENVIRONMENTAL IMPACT



## Classic W

## Water-based protective woodstain

#### COMPOSITION

Water-based product formulated with synthetic resins and transparent iron

### FIELD OF APPLICATION

Suitable for both domestic and professional use as a first coat on raw

wood surfaces of various species, for items intended for exterior or interior use. It features excellent flow and levelling properties, allowing easy application by brush, flow-coating, impregnation systems, or dipping. For maximum outdoor protection under conditions of strong exposure to weathering and sunlight,

the product should be applied as a first coat and overcoated with an acrylic finish in a coloured semi-transparent coating system. Its odourless formulation makes it particularly suitable for use in poorly ventilated environments.

TECHNICAL CHARACTERISTICS OF THE PRODUCT	
APPLICATION	Brush, spray, dipping, impregnation system, flow-coating
SUBSTRATE	Raw or pre-treated substrate, properly sanded
COVERAGE	11-13 m <sup>2</sup> /L per coat
DRYING TIME	Touch dry: 4–6 h – Fully dry: 24 h
DILUTION	Ready to use
APPLICATION CONDITIONS	Application temperature: $+10^{\circ}\text{C}$ to $+30^{\circ}\text{C}$ – Relative humidity: $<65\%$

For more information on the product and the application cycle, refer to the technical data sheet available for download at www.caparreghini.it

### COLOURS AVAILABLE IN STOCK



PACKAGING: 0.75L - 2.5L - 20L - 25L



072 W NOCE CHIARO



CAP ARREGHINI SpA - ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE) Tel. +39 0421 278111 - Fax +39 0421 278115 info@caparreghini.it - www.caparreghini.it Company with Certified Management System UNI EN ISO 9001 - UNI EN ISO 14001

075 W MOGANO





\*The product can be tinted in all shades available in the Novolegno Water-Based

colour chart. The colour chart is available at Cap Arreghini retailers."





