

DESCRIPTION Semi-finished product composed of an aqueous colorant dispersion, for exterior and interior use, and containing micronized pigments that are highly resistant to atmospheric agents and to light.

PROPERTY OF THE PRODUCT		Value	Method
	SOLID BY WEIGHT	27-42%	interior PF25

PERFORMANCE DATA		Value	Method
	SPECIFIC WEIGHT	1150-1400 g/l	interior PF3

SHELF LIFE 1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE Black, Red, Yellow.

TYPICAL USE To use, add to water-based woodstain or water-based polyurethane and acrylic finishes in order to change existing shades or create new ones. The percentage to be used varies from 2-3% for finishing products and from 10-15% for impregnating agents.

THINNING Ready to use.

APPLY +5°C +30°C

INSTRUCTIONS To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.