

DESCRIPTION Semi-finished product composed of solvent-based oily colorant dispersion, for exterior and interior use, and containing micronized pigments that are highly resistant to atmospheric agents and to light.

PROPERTY OF THE PRODUCT	Solid by weight	Value	Method
		073 Dark Walnut 33-37% Yellow, Red 41-45% Black: 48-52%	interior PF25

PERFORMANCE DATA	Specific weight	Value	Method
		900-1150 g/l	interior PF3

SHELF LIFE 1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE Yellow, Red, Black, 073 Dark Walnut.

TYPICAL USE To use, add to solvent woodstain or synthetic solvent-based alkyd finishes in order to change existing shades or create new ones. The percentage to be used varies from 2-3% for finishing products and from 10-15% for impregnating agents.

THINNING Ready to use.

APPLY +5°C +30°C

INSTRUCTIONS To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.