

PRODUCT DATA SHEET
DILUENTE BUTOL

Thinner

DESCRIPTION

Thinner suitable for polyurethane and acrylic paints. Due to its balanced evaporation curve it ensures a uniform smooth and flawless dried film.

**COMPOSITION
SPECIFICATION
DATA**

Product formulated with esters and aromatic hydrocarbons.

	VALUE	METHOD
SPECIFIC WEIGHT	800-900 g/l	Internal PF3

SHELF LIFE

Product is stable till one year as long as it is kept in original and unopened buckets at temperature between +5°C e +30°C.

USE

To be mixed as a diluent with polyurethane and acrylic products used as primer and / or finish. The dosage varies according to the application system and is indicated in the technical data sheet of the relative products.

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary. Our recommendations on the use of the product are based on observations and accurate research carried out on one's own. The experiences gained in the practical application were also taken into consideration. However, due to the enormous variety of supports and application conditions, it is essential to check the suitability of the product and its effectiveness by tests carried out on the specific construction.