

Ecocap

Extra matt washable water-based paint for interiors



Interior washable emulsion paint, matt and anti-glare. Provides a smooth, even finish even on large surfaces backlit, with easy touch-up. Available in a wide range of colors, offering excellent coverage and adhesion on various substrates without the need for a primer: old paints, plasterboard, gypsum finishes, various types of plaster, concrete and fiber cement, and panels of different materials for exhibition stands.

Ideal for use in large spaces where maximum anti-glare performance is required.



linea **ECOLORA**



**HIGH WASH RESISTANCE
EXCELLENT COVERAGE**



**ZERO-GLOSS FINISH
ANTI-GLARE
HIGH COVERAGE**



**LOW ENVIRONMENTAL IMPACT
DIRECT APPLICATION WITHOUT PRIMER
FAST DRYING**



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Ecocap

Extra matt washable water-based paint for interiors

COMPOSITION

APEO-free product formulated with vinyl acetate/acrylate resins in aqueous dispersion and selected fillers

CHARACTERISTICS

Interior washable water-based wall paint with high breathability, easy to apply, with drying times that allow rapid reoccupation of living spaces. Ideal for professional use, offering excellent compatibility, adhesion, filling power, and coverage on various substrates

APPLICATION FIELD

Suitable for decorating and protecting a variety of substrates, including intense colors, achieving excellent aesthetic results at low cost. Applicable on new or maintenance-phase surfaces such as different types of plaster (cement-based, lime-based, premixed), concrete and fiber cement, plasterboard, stucco finishes, old paints, and panels of various materials for exhibition stands. Ideal wherever fast and economical maintenance is desired

AESTHETIC EFFECT

Thanks to good leveling and low splattering, it allows clean and precise application with manual or mechanical tools. The final appearance is elegant and uniform, with opacity that enhances the aesthetic effect and provides visual balance to interior spaces

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Brush, roller, airless spray
SUBSTRATE	Free from dust, properly pretreated
COVERAGE	9–11 m ² /l per coat
GLOSS	<5
DRY SOLID CONTENT BY WEIGHT	55–59% by weight
DRYING TIME	Recoat after 3 h, fully dry in 10 days
DILUTION	Roller, brush: 15–30% with water by volume Airless spray: 0–10% with water by volume Absorbent substrates: first coat 70–100% with water by volume
APPLICATION CONDITIONS	Application temperature: +5°C to +30°C

For more information on the product and application process, please refer to the technical data sheet available at www.caparreghini.it

COLORS AVAILABLE IN STOCK

WHITE.

The color range can be extended with shades from the corresponding color chart and from the Tintoretto, Archipalette, and NCS collections. Colors can be produced using the Arreghini Colors 16 system.

PACKAGING: 1L - 4L - 14L



CAP ARREGHINI SpA - ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with UNI EN ISO 9001 - UNI EN ISO 14001 Certified System

Follow us on



www.caparreghini.it

