

FIBER FINITURA

Opaque dimming effect finish

DESCRIPTION

Water-dilutable paint, moderately breathable, easy to apply, ideal for professional use, with high compatibility, adhesion and workability on different types of substrates.

Suitable for interior use, opaque, odourless, semi-opaque, formulated with acrylic resins in water emulsion, suitable for obtaining special decorations as a finish to be applied over Fiber Fondo.

Since it is odourless, it is particularly suitable for applications in poorly ventilated areas. It is made with raw materials chosen for their low impact, reduced pollution and minimal emissions in order to preserve the well-being and safety of users and people living in the environment.

PRODUCT
PROPERTY

	Value	Method
Water vapour permeability	GOOD	
Impact resistance	EXCELLENT	
Direction of dirt	LOW	
Washing resistance (after 5gg)	EXCELLENT	
Solid by weight	34-38 %	Internal PF25
DRYING	Overcoatable 5-8h; Full 5 days.	Internal PF2

SPECIFICATION
DATA

	Value	Method
SPECIFIC WEIGHT	960-1060 g/l	Internal PF3

SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE

As per samples.

The colour could vary slightly from one production batch to the next; it is therefore important to finish the job with the same batch.

TYPICAL USE

It is ideal as a finish for creating an impressive decorative effect in both in public and private surroundings, where special decorations are required. The substrates used must be skimmed and absolutely smooth.

The texture effect depends on the manual skill of the applicator and on the quantity applied. For this reason the samples are only indicative. Before doing the job, run some tests using a demonstration panel. In order to obtain an even surface, work with the same tool and one applicator only in the finishing phase, and ensure continuous wet-on-wet covering of the entire wall without interruption.

Tools should be washed with water immediately after use.

TOOLS

Roller, Brush Spalter- Brush, Sponge.

THINNING

10-15% with water

COVERAGE

15-18 m²/l per coat.

APPLY

+5°C +30°C

COATING SYSTEM

On concrete, various plasters, new or already painted, rough and irregular, clean the surface to be decorated by removing any parts that are detached and skim with *Jolli* or *Stuccocap*.

On wood, apply Opakite primer o Opakite W and sandpaper.

FIBER FINITURA

Opaque dimming effect finish

On iron substrates, apply a coat of Chromocap or or Chromocap W.
Chromocap can be replaced by Antitruzzine, Corrobloc, Primer Cap
Universale

On substrates prepared as described above and on plasterboard

1. Apply Fiber Fondo, ready to use, with a roller or a brush on wet paint and use the suggested tool for the desired finish.
2. After 8 hours, apply Fiber Finitura or any other decorative of Generation Art line (as Gem, Mineral, Pearl, etc.).

Apply DECOR PROTECTIVE to increase the resistance to abrasion, scratch and washing with detergents and edible liquid.

SPECIFICATION ITEM

Semi-transparent paint for interiors, based on acrylic resins in aqueous emulsion, to apply on several supports or old paintings, pre-emptively treated with Fiber Fondo, with an average consumption of 55 ml/m² in a single layer.

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.