# Gladium

## Professional anti-rust gel enamel



Glossy thixotropic enamel with anti-rust properties, suitable for protecting new or maintenance-phase items made of various materials, used outdoors and indoors. Thanks to its composition and anticorrosive properties, it ensures easy maintenance of iron structures and provides high protection even in aggressive environments.

Ideal for protecting iron, galvanized iron, aluminum, alloys, and plastic items outdoors and indoors, such as frames, railings, tanks, and agricultural equipment, when properly pretreated.

## Linea LASURCAP





LONG-LASTING PROTECTION



RESISTANT TO WEATHERING
HIGHLY IMPACT-RESISTANT FILM
HIGH CORROSION RESISTANCE
EDGE COVERAGE



HIGH AESTHETIC UNIFORMITY
UNIFORM THICKNESS



EXCELLENT BRUSHABILITY

EASY TO APPLY

THIXOTROPIC, NON-DRIPPING AND

NON-SPLASHING

EXCELLENT FLOW AND COVERAGE





### Professional anti-rust gel enamel

#### COMPOSITION

Product formulated with solvent-based alkyd resins, passivating pigments, and light-resistant pigments.

#### **CHARACTERISTICS**

Once applied, it forms a film that provides good water impermeability and high outdoor protection against weathering and solar radiation.

#### FIELD OF APPLICATION

Suitable for both domestic and professional use, ideal for coating systems on various items indoors and outdoors. Can be used as a single

product applied in three coats directly onto new or maintenance-phase ferrous substrates, following thorough cleaning of the item.

| TECHNICAL CHARACTERISTICS OF THE PRODUCT |  |
|--|--|
| APPLICATION                              | Roller, brush, spray   |
| SUBSTRATE                                | Iron, galvanized iron, aluminum, plastic (carefully pre-treated) |
| COVERAGE                                 | 13–15 m²/L for 45 µm dry film                                    |
| GLOSS                                    | Gloss: 65–85   |
| DRYING                                   | Re-coatable: 18 h – Fully dry: 5 days                            |
| DILUTION                                 | Roller, brush: ready to use                                      |
|  | Spray: 0–10% by volume with Thinner VD100                        |
| APPLICATION CONDITIONS                   | Application temperature: +5°C to +30°C                           |

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it

#### COLOURS AVAILABLE IN STOCK



The product can be made in all the shades available in the specific colour chart, available from Cap Arreghini retailers. The colour range can be expanded using the Tintoretto, RAL, and NCS charts.

PACKAGING: 0,750L - 2,5L





**CAP ARREGHINI SpA** ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE) Tel. +39 0421 278111 - Fax +39 0421 278115 info@caparreghini.it - www.caparreghini.it Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001









