

Hydrocap

High quality water-based enamel



Water-based enamel, available in gloss and satin finishes, suitable for long-lasting coating systems on wood, metal, and plastic structures used outdoors or indoors. Its high quality ensures excellent aesthetic and technical results for various coating needs, providing a superior finish along with maximum protection and colour durability outdoors, even under severe weather exposure.

Intended for the protection of structures both outdoors and indoors, such as tables, railings, doors, fences, attics, planters, gazebos, beams, and radiators.

Linea **LASURCAP**



LONG-LASTING PROTECTION



RESISTANT TO WEATHERING AND UV RAYS
DIRECT ADHESION ON GALVANIZED STEEL
HIGHLY ABRASION-RESISTANT FILM
HIGH ADHESION AND COVERAGE



HIGH WHITENESS
HIGH AESTHETIC UNIFORMITY
NON-YELLOWING FINISH
UNIFORM FILM THICKNESS



ADHESION ON VARIOUS SUBSTRATES
EASY TO APPLY
ODOURLESS



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Hydrocap

High quality water-based enamel

COMPOSITION

Product formulated with styrene-acrylic resins in aqueous emulsion and light-stable selected pigments.

CHARACTERISTICS

Hydrocap is formulated with carefully selected, low environmental impact raw materials, providing maximum UV resistance and outdoor protection under conditions of strong exposure to weathering.

FIELD OF APPLICATION

Suitable for protecting new or maintenance-phase items, indoors or outdoors, ensuring a finish with high uniformity and excellent resistance to weathering and mechanical stress. Its adequate elasticity and wear resistance create a film that remains stable, attractive, and durable even under dimensional changes of the substrate due to varying climatic conditions. Features such as good flow, low sagging

tendency, uniform thickness, and edge coverage make it easy to apply, both professionally and in DIY applications.

AESTHETIC EFFECT

Thanks to its formulation, the finish is compact and uniform with a non-yellowing film.


TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Roller, brush, spray
SUBSTRATE	Wood, metal, plastic, galvanized steel, aluminum
COVERAGE	10–12 m ² /L per coat
GLOSS	Gloss: 70–80 – Satin: 30–40
DRYING	Re-coatable: 4 h – Fully dry: 5 days
DILUTION	5–15% by volume with water
APPLICATION CONDITIONS	Application temperature: +15°C to +30°C

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it


COLOURS AVAILABLE IN STOCK

Hydrocap Lucido




BIANCO AC 16


Hydrocap Satin



BIANCO AC 16



RAL 1013



RAL 7035



NERO



RAL 6005



RAL 8016

The colour range can be expanded using the Tintoretto and RAL colour charts.

PACKAGING: 0,750L - 2,5L



CAP ARREGHINI SpA
ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001

Follow us on



www.caparreghini.it

