

DESCRIPTION

Water-based paste formulated with sand, lamellar charges and special binders which make the product extremely hard and elastic. Resins and inert substances are especially resistant to alkaline substrates and atmospheric agents, thus making *K29* the ideal solution to fill holes and cracking and restore any missing material, above all outdoors. *K29* is a fast drying filler that forms a hard and compact mass on which screws and nails grip easily.

PROPERTY OF THE PRODUCT

| | Value | Method |
|------------------------|--------------|---------------|
| Solid by weight | 85-89 % | Interior PF25 |

SPECIFICATION DATA

| | Value | Method |
|------------------------|---------------|---------------|
| Specific weight | 1750–1950 g/l | |
| Drying time | fully 24h | |

SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE

Grey

TYPICAL USE

K29 is applied ready for use on different types of surfaces such as plaster, cement and wood: it is also used for thick coats without posing any risk of cracking. The part that needs to be filled must be preliminarily treated with *Acrilifix*.

TOOLS

Spatula

THINNING

Ready to use.

APPLY

+5°C +30°C

SPECIFICATION ITEM

Water-based paste filler, ideal for filling holes and cracking or fill missing material, especially outdoors, which forms a tough and compact mass on which screws and nails grip easily.

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.