

DESCRIPTION

Odourless solventborne paint for interiors, fairly breathable, easy to apply, with drying times which enable rapid use of the rooms in which it is applied. Ideal for professional use as it is extremely compatible and has excellent adhesion properties, filling powers and covering properties of surface stains caused by various types of pollution such as grease, smoke, nicotine and water infiltration on different types of substrates.

Its good coverage and low tendency to splash mean that it can be applied with manual or mechanical tools which guarantee a finish with excellent visual consistency and an even opacity.

Its quality guarantees an aesthetic and technical solution for a wide range of painting requirements, with an excellent level of finishing. It creates a film with high resistance to stain and dirt penetration, it is resistant to washing with a wet sponge, even using common detergents for easier cleaning.

Having a highly covering power, only one coat is sufficient, in most cases, to cover the primer on condition that they are the same colour.

PRODUCT PROPERTY

	Value	Method
COVERAGE	Excellent	
WHITE POINT	Good	
WASHING RESISTANCE	Good	
VAPOR DIFFUSION	Medium	
Solid by weight	65-69 %	Internal PF25

SPECIFICATION DATA

	Value	Method
Specific weight	1350–1450 g/l	Internal PF3
Drying time	recoatable 5h; fully 5h	Internal PF2
Coverage	95-99%	Internal PF11

SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE

White

TYPICAL USE

It is ideal for decorating and protecting, with pastel shades also, new structures or structures undergoing maintenance that have a variety of substrates such as plasters with different compositions (cement, common lime, premixed), concrete and fibrocement, plasterboard, filler skims and old paint, and in all cases where surfaces fouled with grease, smoke, nicotine need to be covered through quick maintenance, with excellent aesthetic results.

For spray applications, ensure that the substrate is dust-free and avoid excessive atomization of the product by regulating the pressure, nozzle and thinning so as to ensure that the paint sprayed sufficiently wets the surface.

When used for resolving problems caused by nicotine stains, it must not be coated with other paints.

TOOLS

Roller, Brush, Spray.

THINNING

Roller, Brush: 10-15% by volume with odourless thinner *Diluyente Inodore*.

Airless Spray: 5-10% by volume with odourless thinner *Diluyente Inodore*

COVERAGE

8-10 m²/l per coat.

APPLY

+5°C +30°C

COATING SYSTEM

Cement-based, gauged mortar and hydraulic lime-based plasters, , plasterboard, reinforced concrete, new concrete prefabs and old mould-free washable paint

1. Remove any traces of dust, and stop up any imperfections using *Stucco Light* filler.
2. Apply two coats of *Okapa* on a dry substrate, 5 hours apart.

Maintenance of a surface painted with *Okapa*

Wipe any dirt off with a wet sponge. As soon as the substrate is dry, apply one or more coats of *Okapa*.

**SPECIFICATION
ITEM**

Anti-stain paint with a high resistance to washing and a good covering power, at an average consumption rate of 220 ml/m².

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.