Powercap

Water-based acrylic-polyurethane enamel for metal, wood and plastic



Water-based enamel with excellent protective performance, available in gloss, satin, and matte finishes. Suitable for long-lasting coating systems on metal, wood, and plastic structures used outdoors or indoors, it provides outstanding resistance to abrasion and dirt penetration. Its high quality allows direct adhesion to galvanized steel, aluminum, and light alloys. Complies with the requirements of Regulation 852/2004/EC for use in environments where high hygiene and cleanliness standards must be maintained, including areas for handling or storing food products.

Intended for the protection of structures both outdoors and indoors, such as tables, railings, doors, fences, attics, planters, gazebos, beams, and radiators.

LASURCAP









LONG-LASTING PROTECTION



RESISTANT TO WASHING AND COMMON
DETERGENTS AND DISINFECTANTS
HIGHLY ABRASION-RESISTANT FILM
MAXIMUM UV RESISTANCE
HIGH COVERAGE



HIGH WHITENESS
HIGH AESTHETIC UNIFORMITY
NON-YELLOWING FINISH
UNIFORM FILM THICKNESS



DIRECT ADHESION ON GALVANIZED
STEEL, ALUMINUM, PLASTIC
PROTECTS HEALTH AND
THE ENVIRONMENT
EASY TO APPLY
EASILY CLEANABLE



Powercap

Water-based acrylic-polyurethane enamel for metal, wood and plastic

COMPOSITION

Product formulated with polyurethane resins in aqueous emulsion and light-stable selected pigments.

CHARACTERISTICS

is made with low Powercap environmental impact raw materials, ensuring minimal VOC emissions to preserve user well-being and safety while protecting the environment.

FIELD OF APPLICATION

Suitable for protecting new or maintenance-phase items placed outdoors or indoors, providing maximum UV resistance and protection against weathering. Its composition allows treated surfaces to resist abrasion and cleaning with common detergents and antibacterial disinfectants. Excellent coverage and smooth application, both by brush and roller, make it extremely

easy to apply. Being odourless, it is particularly suitable for use in poorly ventilated indoor environments.

AESTHETIC EFFECT

Thanks to its formulation, it ensures a uniform and long-lasting aesthetic appearance, with a non-yellowing finish and high whiteness.

TECHNICAL CHARACTERISTICS OF THE PRODUCT			
APPLICATION	Roller, brush, spray		
SUBSTRATE	Metal, wood, plastic, galvanized steel, aluminum		
COVERAGE	9-11 m²/L per coat		
GLOSS	Gloss: \geq 70 and \leq 75 – Satin: \geq 30 and \leq 40 – Matte: \geq 10 and \leq 15		
DRYING	Re-coatable: 3 h – Fully dry: 10 days		
DILUTION	Ready to use		
APPLICATION CONDITIONS	Application temperature: +15°C to +30°C		

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK

Powercap Lucido	Powercap Satinate)	Powercap Opaco
WHITE	WHITE	ZECCHINO GOLD	WHITE
BLACK	BLACK		BLACK

The colour range can be expanded using the Tintoretto, Tucano, Area 115, Spazio 100, NCS, and RAL colour charts.

PACKAGING: 0,750L - 2,5L





CAP ARREGHINI SpA ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE) Tel. +39 0421 278111 - Fax +39 0421 278115 info@caparreghini.it - www.caparreghini.it Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001

www.caparreghini.it

 $(f)(\bigcirc)(\bigcirc)(in)$

