

Remdur Lucido/Matt

Professional synthetic enamel/ Professional urethane alkyd enamel for universal use



Solvent-based enamel, available in gloss and matte finishes, suitable for long-lasting coating systems on structures made of various materials, used outdoors or indoors. The matte version can be applied directly on surfaces such as wood, hard plastics, alloys, galvanized iron, and aluminum. Its high quality allows for both aesthetic and technical solutions for different coating needs, providing an excellent finish along with maximum protection and colour durability outdoors, even under severe weather exposure.

Intended for the protection of structures both outdoors and indoors, such as tables, railings, frames, grilles, tanks, and agricultural equipment.

Linea **LASURCAP**



LONG-LASTING PROTECTION



RESISTANT TO WEATHERING AND UV RAYS
HIGHLY ABRASION-RESISTANT FILM
HIGH ADHESION AND COVERAGE



HIGH AESTHETIC UNIFORMITY
UNIFORM THICKNESS



ADHESION ON VARIOUS SUBSTRATES (REMDUR MATT)
EASY TO APPLY



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Remdur Lucido/Matt

Professional synthetic enamel/ Professional urethane alkyd enamel for universal use

COMPOSITION

Pigmented product formulated with solvent-based alkyd resins.

CHARACTERISTICS

Remdur is formulated with carefully selected raw materials, ensuring maximum UV resistance and outdoor protection under conditions of strong exposure to weathering. Its adequate elasticity and wear resistance create a film that remains stable, attractive, and durable even under stresses caused by

dimensional changes of the substrate due to varying climatic conditions.

FIELD OF APPLICATION

Suitable for protecting new or maintenance-phase items, indoors or outdoors, providing a finish with high uniformity and excellent resistance to weathering and mechanical stress. Its properties—good flow, low sagging tendency, uniform thickness, and edge coverage—make it easy to apply both professionally and for DIY applications.

AESTHETIC EFFECT

Its high quality allows for an optimal aesthetic and technical solution for various coating needs, delivering an excellent finish along with maximum colour protection and durability outdoors, even under severe weather exposure.

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Roller, brush
SUBSTRATE	Iron, galvanized steel, aluminum, wood, plastic (properly pre-treated)
COVERAGE	Remdur Gloss: 9–11 m ² /L per coat / Remdur Matt: 16–18 m ² /L per coat
GLOSS	Gloss: 85–95, Matte: 15–25
DRYING	Re-coatable: 24 h – Fully dry: 5 days
DILUTION	10% by volume with Thinner VD100
APPLICATION CONDITIONS	Application temperature: +5°C to +30°C

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK

REMDUR LUCIDO



REMDUR MATT



The colour range can be expanded using the AC16 tinting system in the shades of the Tintoretto, Tucano, Spazio 100, Area 115, NCS, and RAL K7 charts. The colour charts are available from Cap Arreghini retailers.



PACKAGING: 0,375 - 0,750L - 2,5L



CAP ARREGHINI SpA

ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001

Follow us on



www.caparreghini.it

made in Italy