Sintech

Aluminum-based enamel



Enamel suitable for the protection of metal structures located outdoors, which, thanks to its formulation with selected aluminium powder, provides excellent weather resistance and high light reflectivity.

Ideal for protecting exterior iron structures such as tanks, silos, towers, or over tar waterproofing.

Linea LASURCAP









ARREGHIN





Aluminum-based enamel

COMPOSITION

Aluminium-based product dispersed in alkyd resins.

CHARACTERISTICS

Thanks to the presence of aluminium powder, once applied, it forms a film

that ensures high UV reflectivity.

APPLICATION FIELD

Suitable for exterior applications on ferrous substrates or over tar waterproofing to achieve high solar reflectance. Particularly recommended in areas where regular maintenance is difficult.

TECHNICAL CHARACTERISTICS OF THE PRODUCT	
APPLICATION	Roller, brush, spray
SUBSTRATE	New or rusted metal (properly prepared)
COVERAGE	13-15 m ² /L
DRYING	Dry film thickness 30 µm - Recoatable after 24 h, full cure 5 days
THINNING	Ready to use
APPLICATION CONDITIONS	Temperature $+5^{\circ}$ C / $+30^{\circ}$ C

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK



ALLUMINIO

PACKAGING: 0,750L - 2,5L





CAP ARREGHINI SpA ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE) Tel. +39 0421 278111 - Fax +39 0421 278115 info@caparreghini.it - www.caparreghini.it Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001 Follow us on







