

Special W Matt

Water-based wax effect finishing



Water-based wax-effect satin finish, available in clear and transparent tinted versions, of the highest quality, suitable for long-lasting coating systems on wooden structures both indoors and outdoors. It provides outstanding mechanical strength, excellent weather and UV resistance, and maximum color stability and durability even under severe exposure conditions. Its high elasticity, compatibility, filling power and adhesion make it suitable for direct application over various types of wood preservatives.

Designed for the protection of exterior wooden structures such as doors, balconies, roof beams, gazebos, pergolas, cladding boards, planters, window frames, verandas and fences.

linea **NOVOLEGNO**



LONG-LASTING PROTECTION
MAXIMUM EXTERIOR COLOUR
DURABILITY



WATERPROOF
HIGH RESISTANCE TO ATMOSPHERIC
AGENTS
HIGH UV PROTECTION
HIGH ELASTICITY



UNIFORM FINISH
ENHANCES THE WOOD GRAIN



ODOURLESS
EXCELLENT FLOW AND COVERAGE
EASY TO APPLY, NON-SAGGING



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Special W Matt

Water-based wax effect finishing

COMPOSITION

Water-based product formulated with acrylic-alkyd resins and transparent iron oxides.

CHARACTERISTICS

Special W Matt is a satin, wax-effect finish that ensures an excellent level of protection and maximum colour durability outdoors, even under severe exposure conditions. It provides good pore wetting with minimal fibre

swelling, allowing direct application over wood impregnating products. Low environmental impact product.

FIELD OF APPLICATION

Suitable for decorating and protecting wooden structures, both new and in maintenance, made from different wood species and exposed to rural, marine or industrial environments. Its good flow, low tendency to sag, uniform thickness and edge coverage make it

easy to apply in both professional and domestic settings. Being odourless, it is particularly suitable for poorly ventilated environments.

AESTHETIC EFFECT

Thanks to its composition, the finish is compact and homogeneous, with a satin wax effect that enhances the natural grain of the wood. The finish remains stable over time

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	roller, brush, aircoat spray
SUBSTRATE	pre-treated, properly sanded, free from oils and resin
YIELD	8-10 m ² /l per coat
GLOSS	±30
DRYING	touch dry 2-3 h, fully dry 6 h
THINNING	brush, roller: up to 10% by volume with water; aircoat spray: ready to use
APPLICATION CONDITIONS	temperature +5°C+30°C

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK



070 W INCOLORE



071 W PINO



078 W QUERCIA



071 W NOCE



078 W CASTAGNO

*The product can be made in all the colours available in the Novolegno water-based colour chart. The colour chart is available at Cap Arreghini retailers.

PACKAGING: 0,750L - 2,5L - 10L



CAP ARREGHINI SpA

ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with Certified Management System UNI EN ISO 9001 - UNI EN ISO 14001

Follow us on



www.caparreghini.it

