

Unifercap W

Water-based micaceous enamel



Water-based ferromicaceous enamel suitable for coating systems on various substrates, for both interior and exterior use, specifically designed for painting iron and galvanized iron. It can be used to decorate different types of surfaces, providing an aesthetically pleasing micaceous effect.

Intended for the protection of structures located outdoors or indoors, such as tables, railings, doors, and gates.

Linea **LASURCAP**



LONG-LASTING PROTECTION



**WEATHER RESISTANCE
HIGH IMPACT-RESISTANT FILM
HIGH CORROSION RESISTANCE
EDGE COVERAGE**



**ANTIQUE-LOOK FINISH
UNIFORM FILM THICKNESS**



**ADHESION ON VARIOUS
SUBSTRATES
DIRECT ADHESION TO ZINC
NON-DRIPPING, NON-SAGGING
SAFE FOR HEALTH AND THE
ENVIRONMENT**



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Unifercap W

Water-based micaceous enamel

COMPOSITION

Product formulated with acrylic-alkyd resins in aqueous dispersion, micaceous iron oxide, and lightfast pigments

CHARACTERISTICS

Its formulation provides a finish with excellent elasticity, scratch and wear resistance, and stability against natural stresses caused by substrate dimensional changes due to climatic variations. Being odorless, it is particularly suitable

for applications in poorly ventilated environments

FIELD OF APPLICATION

Suitable for the protection and decoration of new or maintenance-phase substrates, indoors or outdoors, ensuring maximum UV resistance and protection against atmospheric agents. Provides excellent adhesion on surfaces such as pre-painted wood, rigid plastics, alloys, galvanized steel, and aluminum. Its good flow, low

sag tendency, and fast drying make it easy to apply in both professional and DIY contexts

AESTHETIC EFFECT


Thanks to its composition, it ensures a uniform and long-lasting aesthetic appearance, with maximum colour protection and resistance outdoors, even under severe exposure conditions. Provides an elegant and attractive antiqued effect on surfaces

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Roller, brush, spray
SUBSTRATE	Iron, galvanized steel (properly pre-treated)
COVERAGE	14–16 m ² /L for 35 µm dry film
DRYING TIME	Re-coatable: 8–12 h – Fully dry: 5 days
THINNING	10–15% by volume with water
APPLICATION CONDITIONS	Application temperature: +15°C to +30°C

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK



GRIGIO BASE

*The product can be produced in all shades included in the dedicated colour chart. The colour chart is available at CAP Arreghini retailers.

PACKAGING: 0,750L - 2,5L



CAP ARREGHINI SpA
ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001

Follow us on



www.caparreghini.it

