


Primer Cap Universale

Water-based covering base for all surfaces



Water-based pigmented primer with anticorrosive and adhesion properties suitable for non-absorbent, smooth, and porous surfaces. Its anticorrosive and adhesion characteristics make it a versatile product, suitable for application on various types of substrates positioned indoors and outdoors, such as wooden and metal supports (galvanized iron, aluminum, alloys), plastic, and masonry.

Ideal as a first coat in a water-based pigmented finishing system on structures and objects placed indoors and outdoors, such as railings, radiators, grilles, agricultural equipment, tables, chairs, and masonry.

Linea **LASURCAP**



HIGH ADHESION ON DIFFERENT SUBSTRATES
HIGH COVERAGE
GOOD CORROSION RESISTANCE
DIRECT ADHESION ON GALVANIZED SURFACES



HIGH AESTHETIC UNIFORMITY
UNIFORM FILM THICKNESS



EASY TO APPLY
DRIP-RESISTANT
HEALTH AND ENVIRONMENTALLY FRIENDLY



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Primer Cap Universale

Water-based covering base for all surfaces

COMPOSITION

Product formulated with acrylic resins in aqueous dispersion, corrosion inhibitors, and selected pigments.

FEATURES

It is characterized by fast drying, allowing for rapid execution of the coating. Being odorless, it is particularly

suitable for applications in poorly ventilated indoor environments.

APPLICATION FIELD

Suitable for the protection, in both domestic and professional settings, of new or maintenance-phase substrates, positioned indoors or outdoors. Can be applied on pre-painted wood,


galvanized sheet metal, light alloys, hard plastics, old water-based paints, varnishes, and other smooth surfaces, provided they are properly prepared before application.

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Roller, brush, spray
SUBSTRATE	Substrate: iron, cast iron, galvanized sheet, wood, PVC, masonry (properly prepared)
COVERAGE	Coverage: 8–10 m ² /l per coat
DRYING	Recoat time: 12 h, fully cured in 5 days
THINNING	Thinning: 5–10 % by volume with water
APPLICATION CONDITIONS	Application temperature: +10°C to +30°C

For more information on the product and the application cycle, refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK



BIANCO

PACKAGING: 0,750L - 2,5L



CAP ARREGHINI SpA - ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001

Follow us on



www.caparreghini.it

