

Sil Weiss

Super-matt super-washable super-matt acrylic siloxane water-based paint for interiors



Water-based interior wall paint, washable and extra-matt, easy to apply, with drying times that allow rapid re-use of living spaces. Designed for professional use, it offers excellent compatibility, adhesion, filling power and coverage on various types of substrates.

Ideal for decorating and protecting interior rooms such as kitchens, living rooms and bathrooms.

linea **ECOLORA**



SUPER-WASHABLE
HIGH COVERING POWER
LOW DUST RETENTION



EXTRA-MATT FINISH
HIGH WHITENESS LEVEL
UNIFORM FINISH



ZERO EMISSIONS
EASY TO APPLY
NO DRIPS OR SPLATTERS



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Sil Weiss

Super-matt super-washable super-matt acrylic siloxane water-based paint for interiors

COMPOSITION

APEO-free product formulated with siloxane resins in aqueous dispersion and selected fillers.

CHARACTERISTICS

Low-environmental-impact paint with minimal pollution, formulated with near-zero emissions to safeguard the well-being of users and occupants of the painted environment. The siloxane component

ensures good washability of the film and low dust retention, making it easy to clean with a damp sponge.

FIELD OF APPLICATION

Suitable for the decoration and protection—offering excellent aesthetic results—of new or maintenance substrates made of various materials such as plasterboard, plasters of different compositions, concrete and fibre cement, skim coats and old paints

AESTHETIC EFFECT

Thanks to its quality, it provides an aesthetic and technical solution for diverse painting needs, offering an extremely fine finish. Its high opacity allows for a uniform appearance even on large surfaces under any lighting condition

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Brush, roller, airless spray
SUBSTRATE	Free of dust, properly pre-treated
YIELD	9–11 m ² /l per coat
GLOSS	< 5
SOLID CONTENT	59–63% by weight
DRYING TIME	Recoatable after 3 h, fully dry in 5 days
DILUTION	Roller, brush: 5–15% with water by volume Airless spray: 0–10% with water by volume
APPLICATION CONDITIONS	Temperature +5°C +30°C

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK

White.

The range of colours can be extended to the shades of the Tintoretto and NCS colour charts. Colours can be produced with the Arreghini Colors 16 system

PACKAGING: 4L - 14L



CAP ARREGHINI SpA

ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001

Follow us on



www.caparreghini.it

