

Corrobblock

Epoxy anticorrosive primer



Solvent-based primer suitable for preventing corrosion on iron substrates. Thanks to its excellent adhesion, it is ideal as a bonding primer on galvanized iron, aluminum, light alloys, plastics, and fiberglass. With excellent filling, flow, and coverage properties, it provides a solid base for topcoats and enhances their hiding power.

Intended for the protection of structures and objects located indoors and outdoors, such as railings, window frames, grilles, tanks, agricultural equipment, and industrial machinery.

Linea **LASURCAP**



HIGH CORROSION RESISTANCE
EXCELLENT ADHESION ON VARIOUS
SUBSTRATES

DIRECT ADHESION ON GALVANIZED
SURFACES

FAST DRYING



HIGH AESTHETIC UNIFORMITY
UNIFORM FILM THICKNESS



DIRECT ADHESION ON VARIOUS SURFACES
FILLING POWER AND COVERAGE



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Corroblock

Epoxy anticorrosive primer

COMPOSITION

Based on epoxy-ester resins, selected fillers, and zinc phosphate-based passivating pigments.

CHARACTERISTICS

Once applied, it forms an elastic film that is resistant to dimensional changes

of the substrate caused by varying climatic conditions.

APPLICATION FIELD

Suitable for the protection of new or maintenance-phase metal substrates exposed to highly corrosive agents. Due to its composition and versatility,


it can be overcoated with fast-drying enamels, alkyd enamels, and two-component polyurethane coatings.

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Brush, roller, spray
SUBSTRATE	New or rusted iron, galvanized iron, plastic, fiberglass, light alloys (properly prepared)
COVERAGE	6.5–8 m ² /kg per coat (60 µm dry film)
DRYING TIME	Recoat after 24 h, fully cured in 5 days
THINNING	Spray: 5–10% with Nitro Thinner NV 5000 Brush/roller: 5–10% with Thinner S800
APPLICATION CONDITIONS	Temperature +5°C / +30°C

For more information on the product and the application cycle, refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK



WEISS



SCHWARZ



RAL 3009



RAL 7001

PACKAGING: 0,5Kg - 1Kg - 3Kg



CAP ARREGHINI SpA - ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001

Follow us on



www.caparreghini.it

