

CHARACTERISTICS

Water-repellent, washable wall paint for interiors, with drying times that allow for quick application and immediate use of the rooms.
 Ideal for professional use, it offers high compatibility and adhesion, filling power and coverage on different types of wall surfaces.
 Easy to apply with both manual and mechanical tools, it ensures high homogeneity, uniform opacity and masking of old layers, with excellent aesthetic and technical performance. With low dust retention, the film created by *Extra White* is still easy to clean with a damp sponge.

COMPOSITION

APEO-free product based on vinylversatic resins in aqueous dispersion and selected aggregates.

PRODUCT PROPERTIES

	Class EN13300	Method	Value
Shine	Very matt	UNI EN ISO 2813	Gloss < 5
Dirt pick-up	Low	UNI 10792	$\Delta L > 3$ and ≤ 9
Coverage	2	UNI EN ISO 6504-3	≥ 98 and < 99.5
Wet scrubbing resistance	3	UNI EN ISO 11998	$\geq 20 L_{dft} < 70 \mu$
Dry residue by weight		Internal PF25	65-69
Drying		Internal PF2	Recoatable 2-3 hours Complete 5 days

SPECIFICATIONS

Specific weight	Indoor PF3	1560–1660 g/l
------------------------	------------	---------------

STORAGE

The product is stable for 1 year if stored in its original containers at a temperature between +5°C and +30°C.

COLOURS

White.

USE

It is suitable for decorating and protecting, even with pastel colours, with excellent aesthetic results and low costs, on plasters of various compositions, whether new or undergoing maintenance. When spray applying, ensure that the substrate is free of dust and avoid excessive atomisation of the product by adjusting the pressure, nozzle and dilution to ensure that the paint adequately wets the surface. For surfaces subject to biological contamination from mould, add 2 litres of *A10* for every 14 litres of paint.

TOOLS

Roller, brush, spray.

DILUTION

Roller, brush: 20-30% with water by volume.
 Airless spray: 0-10% with water by volume.

COVERAGE

8-10 m²/l per coat

APPLICATION TEMPERATURE

+5°C +30°C

PAINTING SYSTEM

Cementitious plasters, bastard mortar or hydraulic lime plasters, stucco skim coats, plasterboard, reinforced concrete, new and old washable paints free from mould

1. Remove all traces of dust and fill any holes with *Stucco Light*.
2. On a dry and clean surface, apply two coats of *Extra White*, waiting 3-4 hours between coats.

Gypsum skim coats, tempera paints and other highly absorbent substrates

First apply a coat of *Acrilifix* diluted 1:5 with water or a coat of *Coprisol*.

The degree of absorption of a tempera paint can be assessed as follows: after applying the first coat of paint, observe the surface: if numerous air bubbles form, absorption is excessive and it is necessary to proceed as for plaster skim coats or completely remove the previous paint by wetting it thoroughly with water and scraping it off with a spatula.

Maintenance on a surface painted with *Extra White*

Clean the dirt with a damp sponge and, once dry, apply one or more coats of *Extra White*.

SPECIFICATION ITEM SPECIFICATION

Water-repellent washable water-based paint for interiors based on synthetic resins with 67% solid residue, classified according to EN 13300 with class 2 coverage, low dirt pick-up, very matt opacity, to be applied with an average consumption of 220 ml/m².

WARNINGS

To carry out the work in a workmanlike manner, it is essential to follow the instructions for surface preparation contained in the CAP Arreghini Books.

The specification data was determined at +23°C with 65% relative humidity. Under different conditions, the data and the times between one operation and another may vary.

The technical information contained herein is indicative. Due to the enormous variety of substrates and application conditions, it is advisable to check the suitability of the product for use and its effectiveness by carrying out tests on the specific application.