Sil96 Tex Active

Acrylic-siloxane anti-mould, anti-algae smoothing finish for exterior use



Rough textured wall finish for exteriors formulated with acrylic-siloxane resins in aqueous dispersion and medium-sized aggregates. Ideal for renovating uneven and irregular surfaces or for repairing the exterior surfaces of historic buildings.

The product provides an exterior protective coating on buildings in historic centres or in areas that are particularly exposed to weathering where good colour retention and protection are required.

Linea FASADECAP



LONG LASTING EXTERIOR COLOUR STABILITY



WEATHER-RESISTANT
WATER VAPOUR DIFFUSION
RESISTANCE TO WATER PENETRATION



OPAQUE FINISH
HIGH HIDING POWER



ARREGHINI

il96 Active

EASILY APPLICABLE UNIFORMING



Sil96 Tex Active

Acrylic-siloxane anti-mould, anti-algae smoothing finish for exterior use

COMPOSITION

Product formulated with acrylic and siloxane styrene resins in aqueous dispersion and selected aggregates.

CHARACTERISTICS

The product is characterized by a balance between the resistance to water penetration and water vapour

diffusion, making it breathable so that the walls are kept dry. Given the excellent quality-price ratio, it is the ideal solution for large works

FIELD OF APPLICATION

The product is used on various types of plasters or old coatings as a finish to protect building façades, by applying two coats with a roller.

AESTHETIC EFFECT

Thanks to the opacity and high hiding power of the product, any imperfections in the substrate are filled and covered to deliver an even and compact finish.

TECHNICAL FEATURES OF THE PRODUCT	
APPLICATION	roller
SUBSTRATE	different types of plasters, old coatings
COVERAGE	2 - 2,5 m²/kg per coat
DRYING TIME	recoating time 5 hours, completely dry 5 days
THINNING	up to 10% by weight with water
APPLICATION TEMPERATURE	temperatura +5°C +30°C

For more information on the product and application, please refer to the technical data sheet that can be downloaded from the website www.caparreghini.it

	1

COLOURS IN STOCK

The range of colours can be extended to include pastel shades. The colours can be produced with the Arreghini Colors 16 system.

CAN/TUB SIZES: 25Kg





CAP ARREGHINI SpA ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE) Tel. +39 0421 278111 - Fax +39 0421 278115 info@caparreghini.it - www.caparreghini.it Company with Certified System UNI EN ISO 9001 - UNI EN ISO 14001 Follow us on







