

**DESCRIPTION** Quick-drying paint to be mixed with wood powder for grouting wooden floors.

**COMPOSITION** Product formulated with synthetic resins and nitrocellulose.

**PROPERTIES OF THE PRODUCT**

	VALUE	METHOD
DRYING	FAST	
SOLID BY WEIGHT	8-12 %	Internal PF25
DRYING	Overcoatable 1 h	Internal PF2
	Complete 5 days	

**SPECIFICATION DATA**

	VALUE	METHOD
SPECIFIC WEIGHT	850-950 g/l	Internal PF3

**SHELF LIFE**

Keep the tin hermetically sealed in a cool dry place with temperatures of between +5°C and +30°C, away from fire sources. The P120 component must be kept dry. For this reason, once the tin has been used, ensure that it is then re-closed hermetically and that the air volume is not superior to 1/3 of the total volume. If this is not the case, either use the product within a short period of time or transfer it to a smaller tin.

**COLOUR RANGE**

Transparent colourless

**USE**

Wooden flooring. Use fine powders in as large quantities as possible, as this improves the subsequent sandpapering phase. *Stucco per Parchetti* filler, especially on dark woods, must be well sandpapered in order to avoid different shades.

**TOOLS**

Steel spatula.

**THINNING**

Mix with wood powder until a thick paste is formed.

**APPLICATION TEMPERATURE**

+5°C +30°C

**SPECIFICATION ITEM**

Transparent nitrosynthetic paint with a solid residue of 10% to be mixed with wood powder and used as a filler for wooden flooring.

**INSTRUCTIONS**

To carry out the work in a proper way, it is of fundamental importance to follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books, in the application cycle and in the product data sheet.

This technical information is intended as a rough guide. Adapt the instructions to the specific conditions of use. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between one operation and the next vary.

Our recommendations on the use of the product are based on accurate observations and research carried out by us. The experience gained in practice was also taken into consideration. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and its effectiveness by testing on the specific case.