

My Weiss Active

Water-repellent, washable, anti-mould, matt water-based paint for interiors



Washable, water-repellent interior wall paint with a matte finish and excellent whiteness, enhanced with a fungicide to provide effective protection against various types of mold. Suitable for interior spaces, it ensures a smooth and uniform finish, ideal for covering old paint layers, even on large surfaces and under different lighting conditions. Thanks to its hygienic properties and washability, it requires minimal maintenance while keeping the treated surface looking pristine for a long time.

Perfect for protecting the entire home, it delivers excellent performance, especially in rooms such as bathrooms and kitchens.

Linea **SANACAP**



HIGH COVERING POWER
GOOD WASHING RESISTANCE
FAST DRYING



MATTE FINISH
UNIFORM FINISH



EASY TO APPLY
UNIFORM MATTE FINISH
EVEN ON LARGE SURFACES



ARREGHINI®
ITALIAN PAINTS SINCE 1950

My Weiss Active

Water-repellent, washable, anti-mould, matt water-based paint for interiors

COMPOSITION

APEO-free product based on vinyl-versatic resins in aqueous dispersion and selected fillers.

FEATURES

Washable, water-repellent interior paint with excellent filling power, coverage, and fast drying, allowing for quick application while achieving

a high-quality aesthetic result

APPLICATION FIELD

Suitable for decorating and protecting various types of plaster, both new and under maintenance, made of different materials such as drywall and traditional plasters, delivering excellent aesthetic results at a contained cost.

AESTHETIC EFFECT


Its properties ensure a uniform matte finish, even on large surfaces, combining excellent aesthetic and technical performance. The film created by My Weiss Active is easy to clean with a damp sponge due to its low dust retention

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Roller, brush, spray
SUBSTRATE	Drywall, various plasters, and old paints
CLASS	Class 3
COVERAGE	9–10 m ² /l per coat
GLOSS	<5 very matte
DRY RESIDUE	65–69% by weight
DRYING	Overcoatable in 2–3 h, fully cured in 5 days
THINNING	Roller, brush: 20–30% with water by volume Airless spray: 0–10% with water by volume
APPLICATION CONDITIONS	Application temperature: +5 °C to +30 °C

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK



WHITE

The range of colors can be expanded with pastel shades. Colors can be produced using the Arreghini Colors 16 system.

PACKAGING: 4L - 14L



CAP ARREGHINI SpA

ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001

Follow us on



www.caparreghini.it

