

Mont Blanc

Extra-matte washable acrylic-siloxane interior paint



Washable water-based acrylic-siloxane interior wall paint, featuring high breathability and easy application, with drying times that allow for rapid use of living spaces. Ideal for professional use due to its excellent compatibility, adhesion, filling power, and coverage on various types of substrates.

Perfect for decorating and protecting interior spaces such as kitchens, living rooms, and bathrooms.

linea **ECOLORA**



WASHABLE
HIGH COVERING POWER
LOW DUST RETENTION



EXTRA-MATTE FINISH
HIGH WHITENESS
UNIFORM FINISH



LOW ENVIRONMENTAL IMPACT
EASY TO APPLY
DRIP- AND SPLASH-FREE



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Mont Blanc

Extra-matte washable acrylic-siloxane interior paint

COMPOSITION

APEO-free product formulated with acrylic-siloxane resins in aqueous dispersion and selected fillers.

FEATURES

Low environmental impact paint with minimal pollution, formulated to achieve near-zero emissions to protect the health of users and occupants. The acrylic-siloxane component ensures good washability and low dust retention, making the film easy to clean with a

damp sponge.

APPLICATION FIELD

Suitable for decorating and protecting surfaces, including pastel shades, delivering excellent aesthetic results at a low cost. Applicable on new or maintenance substrates made of various materials such as plasters of different compositions (cement-based, lime-based, pre-mixed), concrete and fiber cement, drywall, stucco finishes, old paints, panels for exhibition stands,

and in all cases where quick and economical maintenance is desired

AESTHETIC EFFECT

Its quality provides an optimal aesthetic and technical solution for different painting needs. High opacity ensures a uniform appearance even on large surfaces under any lighting conditions.

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Brush, roller, airless spray. Dust-free, properly pretreated substrate
SUBSTRATE	9–11 m ² /l per coat
COVERAGE	<5
GLOSS	65–69% by weight
DRY RESIDUE BY WEIGHT	Overcoatable in 3 h, fully cured in 5 days
DRYING	Roller, brush: 15–30% with water by volume
THINNING	Airless spray: 0–10% with water by volume Absorbent substrates: first coat 70–100% with water by volume
APPLICATION CONDITIONS	Application temperature: +5 °C to +30 °C

For more information on the product and the application process, please refer to the technical data sheet available for download at www.caparreghini.it

COLOURS AVAILABLE IN STOCK

White.

The color range can be expanded with shades from the Tintoretto palette. Colors can be produced using the Arreghini Colors 16 system.

PACKAGING: 4L - 14L



CAP ARREGHINI SpA

ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Company with Certified Management System UNI EN ISO 9001 – UNI EN ISO 14001

Follow us on



www.caparreghini.it

