

Techcoat Pro

Transparent protective two-component finish



Transparent two-component acrylic paint, non-yellowing, water-repellent, suitable for indoor and outdoor use for the protection of micro cement surfaces or finished with decorative effects (including lime-based decorative finishes). Techcoat Pro guarantees high resistance to water, abrasion, stomping and scratches.

Ideal in the field of civil construction for private or commercial use such as shops, apartments, hotels, showrooms, offices, museums and public buildings.

Linea **GENERATION ART**



GREAT ELASTICITY
EXCELLENT RESISTANCE TO WASHING
FAST DRYING



**GLOSSY, SEMI-GLOSSY
AND MATTE FINISH**
HOMOGENEOUS FINISH



EASY TO APPLY
HOMOGENEOUS OPACITY
ON LARGER SURFACES



ARREGHINI®
ITALIAN PAINTS SINCE 1950

Techcoat Pro

Transparent protective two-component finish

COMPOSITION

Product formulated with fine hydroxyl acrylic resins in aqueous emulsion, selected opacifiers and aliphatic polyisocyanate.

CHARACTERISTICS

Transparent two-component acrylic paint, non-yellowing, water-repellent, suitable for indoor and outdoor use. Techcoat Pro guarantees high resistance to water, abrasion, stomping and scratches.

FIELD OF USE


It is used for the protection of micro-cement surfaces and decorative coatings, including lime-based products, on vertical and horizontal surfaces. Techcoat Pro must be applied in double layers.

TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Roller, brush, spray.
SURFACE	Micro cement decorative finishes (also lime-based)
YIELD	6.5 -7 m ² /l in double layer (cons. rate: 150 g/m ² x 2 layers)
GLOSS	gloss, semigloss, matt
DRY RESIDUE	Comp. A: 32% ± 2 and A + B: 40% ± 2
DRYING TIME	stackable 4h, complete 5 days
MIXING RATIO	100:25 with Induritore 1 in weight and in volume
DILUTION	10% in volume with water
APPLICATION TEMPERATURE	+15°C +30°C

For more information on the product and the application cycle, consult the technical data sheet downloadable from www.caparreghini.it.

COLORS AVAILABLE IN STOCK



TRANSPARENT | CLEAR

PACKAGING: 4L



CAP ARREGHINI SpA

ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

info@caparreghini.it - www.caparreghini.it

Azienda con Sistema Certificato UNI EN ISO 9001 - UNI EN ISO 14001

follow us on



www.caparreghini.it

